

REBAR STRAIGHTENER



DIAMOND[®]

A dual-purpose tool that cleanly straightens bents rebars and function as a simple bender.

Accepts any 450N/mm² tensile strength rebar up to 32mm (1¼")

DBR-32WH  



optional bending hook

SPECIFICATIONS

Model	DBR-32WH
Max. rebar diameter	32mm (1 ¼")
Bending speed	4sec /90°
Max. tensile strength	450 N/mm ²
Bending angle	Up to 144°
Power supply	Electric motor
Voltage	AC 100V/115V/230V
Power input	1050W (1.4HP)
Weight	26 kg
Dimension (mm)	660x270x200



PULL



PUSH



PUSH

Rebar diameter	Straightening capacity		Bending capacity	
	Push	Pull	Push	Pull
13mm (1/2")	up to 125°	up to 121°	up to 94°	up to 90°
16mm (5/8")	128°	124°	90°	90°
20mm (3/4")	130°	126°	90°	90°
25mm (1")	132°	124°	90°	90°
29mm (1 1/8")	140°	135°	90°	90°
32mm (1 1/4")	144°	138°	90°	90°



Maximum diameter



Weight

Contact: Trading Department, Sanko Fastem (Thailand) Ltd.,
TEL: 662-516-9823-5, Email: trading@sanko.co.th